



# COLLISION & CRIME

FORENSIC  
SOLUTIONS<sup>LLC</sup>

## Leica TS13 Data sheet



Sometimes you need your instrument to grow with your projects. The **Leica TS13** empowers you to start with two-person mode and upgrade the instrument gradually to a robotic total station. You decide when to upgrade it – you can choose a different **keyboard**, add **lock** to follow a moving target or include **robotic capabilities** with **SpeedSearch** and controller **connectivity** via a radio handle. The TS13 comes with **AutoHeight**, helping you to setup your instrument error-free.

### LEICA TS13 TOTAL STATION: COLLECT IT.

- **Efficient data collection for mapping projects:** measurements, adjustments, and computations – all supported by powerful coding and linework routines.
- **Easy-to-use and data-centric field software:** efficient data collection, management, visualisation, import and export.
- **Upgradeable total station for measurement and layout tasks:** starting with two-person, scalable to one-person operation.
- **Accurate and effective stakeout and construction measurements:** automated routines for both two-person and one-person design data layout, as-built checks, and BIM tasks.

- when it has to be **right**

**Leica**  
Geosystems

# Leica TS13 Total Station

## Basic variant



### ANGLE MEASUREMENT

Accuracy <sup>1</sup> Hz and V	■ Absolute, continuous, diametrical	1" (0.3 mgon), 2" (0.6 mgon), 3" (1 mgon), 5" (1.5 mgon)
--------------------------------	-------------------------------------	--

### DISTANCE MEASUREMENT

Range <sup>2</sup>	■ Prism (GPR1, GPH1P) <sup>3</sup> ■ Non-Prism / Any surface <sup>4</sup>	0.9 m to 3,500 m R500: 0.9 m to >500 m R1000: 0.9 m to >1,000 m
Accuracy / Measurement time	■ Single (prism) <sup>2,5</sup> ■ Single (prism fast) <sup>2,5</sup> ■ Single (any surface) <sup>2,4,5,6</sup>	1 mm + 1.5 ppm / typically 2.4 s 2 mm + 1.5 ppm / typically 1.5 s <sup>10</sup> 2 mm + 2 ppm / typically 2 s <sup>9</sup>
Laser dot size	At 50m	8 mm x 20 mm
Measurement technology	System analyser	Coaxial, visible red laser

### AUTOMATIC AIMING - ATR

Target aiming range <sup>2</sup>	■ Circular prism (GPR1, GPH1P) ■ 360° prism (GRZ4, GRZ122)	■ 1,000 m ■ 800 m
Accuracy <sup>1,2</sup> / Measurement time	ATR angle accuracy Hz, V	1" (0.3 mgon), 2" (0.6 mgon), 3" (1 mgon), 5" (1.5 mgon) / typically 3-4 s

### GUIDE LIGHT (EGL)

Working range / Accuracy	5 - 150 m / typically 5 cm @ 100 m
--------------------------	------------------------------------

### GENERAL

Processor	TI OMAP4430 1 GHz Dual-core ARM® Cortex™- A9 MPCore™	
AutoHeight module for automatic instrument height measurement	■ Distance accuracy ■ Distance range	1.0 mm (1 Sigma) 0.7 m to 2.7 m
Power management	Exchangeable Lithium-Ion battery	Operating time up to 8 h
Field software	Leica Captivate with apps	Running on field controller
Data storage	■ Internal memory 2 GB ■ SD card 1 GB or 8 GB	On field controller
Interfaces	RS232, USB, Bluetooth®, WLAN	
Weight	Total station including battery	5.0 kg
Environmental specifications	■ Working temperature range ■ Dust / Water (IEC 60529) / Humidity	■ -20°C to +50°C ■ IP55 / 95%, non-condensing

## Upgrades<sup>7</sup>



### KEYBOARD DISPLAY UNIT (Optional)

Keyboard with display	Face I and face II optional	5" (inch), WVGA, colour, touch 25 keys, illumination
Field software	Leica Captivate including apps	Running on TS13 instrument
Data storage	Internal memory 2 GB SD card 1 GB or 8 GB	On TS13 instrument
Weight	Total station including battery	5.3 kg

### TARGET LOCK (Optional)

Target locking range <sup>2</sup>	■ Circular prism (GPR1, GPH1P) ■ 360° prism (GRZ4, GRZ122)	■ 800 m ■ 600 m
-----------------------------------	---	--------------------

### ROBOTIC SURVEYING including PRISM FAST SEARCH (Optional)<sup>11</sup>

SpeedSearch range / Search time	360° prism (GRZ4, GRZ122)	300 m / Typically 7 s
Robotic range with long-range Bluetooth® <sup>8</sup>	To CS20 internal long-range Bluetooth® To CTR20 expansion pack	500 m 1,000 m

<sup>1</sup> Standard deviation ISO 17123-3

<sup>2</sup> Overcast, no haze, visibility about 40 km, no heat shimmer

<sup>3</sup> 0.9 m to 2,000 m for 360° prisms (GRZ4, GRZ122)

<sup>4</sup> Object in shade, sky overcast, Kodak Gray Card (90% reflective)

<sup>5</sup> Standard deviation ISO 17123-4

<sup>6</sup> Distance > 500 m: Accuracy 4 mm + 2 ppm, Measurement time typically 6 s

<sup>7</sup> Initial or after sales, independent from each other

<sup>8</sup> Under good radio conditions

<sup>9</sup> Up to 50 m, max. measurement time 15 s for full range

<sup>10</sup> Initial measurement time typically 2 s

<sup>11</sup> Available also without prism fast search



Laser radiation, avoid direct eye exposure.  
Class 3R laser product in accordance with IEC 60825-1:2014.

The Bluetooth® trademarks are owned by Bluetooth SIG, Inc. Windows is a registered trademark of Microsoft Corporation. Other trademarks and trade names are those of their respective owners. Copyright Leica Geosystems AG, 9435 Heerbrugg, Switzerland. All rights reserved. Printed in Switzerland - 2020. Leica Geosystems AG is part of Hexagon AB. 929650en - 11.20



**Integrate with LOC8 – Lock & Locate**

For more information visit: [leica-geosystems.com/LOC8](http://leica-geosystems.com/LOC8)



**COLLISION & CRIME**  
FORENSIC SOLUTIONS  
Forensic Reconstruction / Investigations / Certified Training

www.CollisionFS.com  
**Michael Selves**  
**Collision Forensic Solutions**  
300 South Fillmore St.  
Papillion, NE 68046  
PH: (402-339-1518)